

Order Information					
DAC					
Model	Rate	Interface	Sort	Cable Diamter	Transmission Distance
FI-DAC10-**M	10Gb/s	SFP+ to SFP+	Passive	**AWG(24/30 optional)	24AWG<10m, 30AWG<3m
FI-DAC10-**M-ACT	10Gb/s	SFP+ to SFP+	Active	**AWG(24/28/30 optional)	24AWG<15m, 28AWG<10m, 30AWG<3m
FI-DAC25-**M	25Gb/s	SFP28 to SFP28	Passive	**AWG(26/28/30 optional)	26AWG<5m, 28AWG<3m, 30AWG<3m
FI-DAC40-**M	40Gb/s	QSFP+ to QSFP+	Passive	**AWG(26/30 optional)	26AWG<7m, 30AWG<3m
FI-DAC40-**M-4SFP+	40Gb/s	QSFP+ to SFP+	Passive	**AWG(26/30 optional)	26AWG<7m, 30AWG<3m
FI-DAC100-**M	100Gb/s	QSFP28 to QSFP28	Passive	**AWG(26/30 optional)	26AWG<5m, 30AWG<3m
FI-DAC100-**M-4SFP28	100Gb/s	QSFP28 to SFP28	Passive	**AWG(26/30 optional)	26AWG<5m, 30AWG<3m
Remark: Above "**M" refers to the corresponding meters.					
Copper					
Model	Rate	Transmission Distance	Interface		
FI-SFP01-T-01	100M	100M	RJ45		
FI-SFP10-T-01	1000M	100M	RJ45		
FI-SFPAU-T-01	10/100/1000M	100M	RJ45		
FI-SFP+10-T-003	10G	30M	RJ45		